

Product Description

OMV gear oil LDI SAE 75W-80

Product number: 183620

OMV gear oil LDI SAE 75W-80 is a synthetically based high-performance multigrade gear oil especially for manual transmissions of ZF with or without intertarders of busses and trucks.

Properties

- Very good aging-stability
- Suitable for extended oil drain intervals
- High corrosion prevention
- Excellent lubrication properties
- Best extreme pressure-stability
- Excellent viscosity-temperature behaviour
- Extremely low pour point

Application

OMV gear oil LDI SAE 75W-80 is recommended for extended oil drain intervals especially for synchronized manual transmissions with or without intertarders.

Specifications

API GL-4, MAN 341 Typ Z-3

Approvals

MAN 341 Typ E-3; ZF TE-ML 02D, 08

Technical data (based on typical production data)

Property	Unit	OMV gear oil LDI SAE 75W-80
Density/15°C	Kg/m ³	879
Flash point COC	°C	230
Viscosity class	SAE	75W-80
Viscosity/40°C	mm ² /s	66
Viscosity/100°C	mm ² /s	9.5
Pour point	°C	< -39

A viscosity/temperature diagram is available on request.

Safety, health, environment

A data sheet with safety and health information can be found on the Internet at www.omv.com.

Used lubricants and empty containers must be disposed of in accordance with environmental regulations.