

OMV lube P 150 is a lubricating oil based on high quality solvent neutrals.

Properties

OMV lube P 150 is a stable lubricating oil with good viscosity-temperature behaviour (VI>90) and very good lubricating properties.

Application

OMV lube P 150 is widely used in gears, roller and glider bearing lubrication, in circulating systems, for loss-lubrication and as a high quality rinsing oil for heat transfer and turbine oil systems.

Specification

Lubricating oil DIN 51 517 – C

Lubricating oil DIN 51 501 – L-AN

Lubricating oil DIN 51 502 – H

Technical data (typical values)

Property	Unit	OMV lube P 150
Density/15°C	kg/m ³	890
Flash point COC	°C	>260
Pour point	°C	<-12
Viscosity/40°C	mm ² /s	150
Viscosity/100°C	mm ² /s	14,5

A viscosity temperature diagram can be submitted on request.

Safety, health, environment

A data sheet with safety and health information can be found on the Internet at

www.omv.com.

Used lubricants and empty containers must be disposed of in accordance with environmental regulations.

All data are average values and are subject to production-related fluctuations. Technical data are subject to change.

Please observe the instructions of the machine manufacturers!

Further information can be obtained from Technical Marketing Service Lubricants technics.lubes@omv.com.