

Product Data Sheet

Mobil ATF 200 Automatic Transmission Fluid (Type A Suffix A)

Product Description and Application

Mobil ATF 200 was originally developed to meet the requirements of General Motors (now obsolete) automatic transmission fluid specification - Type A, Suffix A (TASA). It is formulated to function as a power transmission fluid in torque converters, a hydraulic fluid in control and servo systems, a lubricant for bearings and gears, a friction controlling medium for the bands and clutches and a heat transfer medium to carry heat generated in transmissions to the gear case or oil cooler.

Due to its high Viscosity Index Mobil ATF 200 undergoes relatively small changes in fluidity regardless of operating or ambient temperatures. This ensures excellent performance as a hydraulic medium giving good operation under high temperature conditions and minimum power losses under cold conditions. The low pour point ensures prompt circulation at low starting temperatures to provide proper lubrication of the transmission working parts. The oxidation resistant and detergent properties reduce the possibility of deposit formation and lacquering on component parts which can interfere with correct operation of the transmission unit and its control system.

Mobil ATF 200 has very good foam resistance and anti-wear properties for planetary gears and thrust washers. Smooth transmission operation depends upon perfect synchronisation of engagement and release as the load is transferred from one unit to another. The correct transition from complete lubrication as the bands of clutches are disengaged to a frictional contact sufficient to hold or transmit power, demands the use of a very light fluid having extremely high lubricating properties. Mobil ATF 200 contains special additive material which ensures maximisation of this characteristic.

Mobil ATF 200 is recommended for passenger car and light commercial vehicle automatic transmissions as well as power steering systems and other hydraulic applications. It is also suitable for hydraulic systems in farm equipment.

Benefits

Mobil ATF 200 offers the following benefits:

- Correct frictional characteristics give smooth transmission and perfect synchronisation, over a long period under continual severe operating conditions
- Protection against deposit formation and evaporation losses at high operating temperatures with very good low temperature operation
- Good protection against wear, resistance to rust, corrosion and foam
- Compatible with seal materials used in transmission units
- Lower maintenance costs, and improved operating profits

Specifications

Mobil ATF 200 meets the following specifications:

Allison C-3 fluid for Power Shift transmissions

GM automatic transmission fluid specification - Type A, Suffix A (TASA), now obsolete

Mercedes Benz Sheet 236.2, covering on/off-highway vehicles

Health and Safety

Based on available toxicological information, it has been determined that this product poses no significant health risk when used and handled properly.

Details on handling, as well as health and safety information, can be found in the Material Safety Data Bulletin which can be obtained through Mobil Oil Company Ltd., by telephoning 01372 22 2000.

Typical physical characteristics are given in the table. These are intended as a guide to industry and are not necessarily manufacturing or marketing specifications.

Typical Characteristics

	Mobil ATF 200
Relative Density 15/4 °C	0.887
Viscosity, cSt at 40°C	43.8
Viscosity, cSt at 100°C	7.9
Viscosity Index	153
Pour Point, °C max.	-42
Flash Point, °C min. COC	188
Colour, ASTM	Red

Due to continual product research and development, the information contained herein is subject to change without notice.

Mobil Oil Company Limited
Acting as Agent for Mobil Lubricants UK Limited
ExxonMobil House, Ermyn Way
Leatherhead, Surrey, KT22 8UX
Telephone: 01372 22 2000

