

Cut-Max SE2

Multi-purpose dielectric fluid for spark erosion

DESCRIPTION

Cut-Max SE2 is a transparent, very low odour, low viscosity dielectric fluid for superfine finishing operations.

APPLICATION

Cut-Max SE2 is specialist fluid for EDM machining and is especially designed for superfine finishing operations.

Main applications include machining of moulds for die-casting or plastic injection machines and in aerospace turbine blade production. Cut-Max SE2 is used for fine boring of aerofoil honeycombs in nickel alloys. e.g. Inconel 718. Cut-Max SE2 has Rolls Royce CSS 142A approval.

Cut-Max SE2 can be used on individual machines and in centralised systems.

ADVANTAGES

- ❑ Very low odour and smoke-free operation for operator preference
- ❑ Efficient flushing of spark debris minimising micro-soldering between component, swarf and electrode.
- ❑ Very low viscosity for fine surface finish
- ❑ Suitable for all types of filtration including diatomaceous earth
- ❑ Highly resistant to oxidation for long service life

STORAGE

Product should be stored under cover in clean, dry conditions and protected from frost. Recommended storage temperature is between 5°C and 35°C. Use stock in delivery rotation. A shelf life of twelve months can be anticipated.

TYPICAL PHYSICAL PROPERTIES

TEST	TYPICAL VALUE	TEST METHOD
Appearance	Amber oil	
Specific gravity @ 20°C	0.78	DIN 51757
Viscosity @ 40°C, mm ² /s	1.8	DIN 51562
Viscosity @ 20°C, mm ² /s	3.0	DIN 51562
Flash Point °C	78	DIN ISO2592
Copper Corrosion	1a	DIN 51759

HEALTH AND SAFETY

Health and Safety Data Sheets are supplied to customers to comply with Section 6 of the Health and Safety at Work Act 1974, and should be closely studied prior to handling or use of the product. Copies are available from your Technical Health and Safety Officer. Various other advisory publications are available from the Health and Safety Executive and Her Majesty's Stationery Office.

Revision no. 1
05/07

All data given in this Product Data Sheet are typical of this material. It does not however constitute a specification. We reserve the right to modify products without prior notice. All products, services and information supplied are provided upon the terms of our standard Conditions of Sale from time to time in force.

Houghton plc

Beacon Road Trafford Park Manchester M17 1AF

Tel +44(0) 161 874 5000

Fax +44(0) 161 874 5001

E-mail uk.enquiries@houghtoneurope.com



HOUGHTON™