

OKS 2801 Leak Detector, Spray



Description

Leak detector for locating of leaks on lines, apparatuses and containers under internal pressure.

Applications

- Piping and hoses, for example steel bottles, compressors, breathing devices, oxyacetylene gas and inert-gas arc welding devices and burners
- Fittings, flanges, valves, screwed connections, soldered and welded connections of pressure gas systems and lines
- Suitable for compressed air, refrigerant, acetylene, butane, natural gas, carbon dioxide, gaseous oxygen, propane, town gas, nitrogen, hydrogen and, ammonia

Advantages and benefits

- Acts non-corrosive
- Allows direct visual inspection of the leakage point through bubble formation
- Tested by the DVGW in accordance with DIN EN 14291
- Suitable for spraying overhead

Branches

- Paper and packaging industry
- Chemical industry
- Rubber and plastic processing
- Logistics
- Maintenance and servicing
- Plant and machine (tool) engineering
- Glass and foundry industry
- Shipbuilding and marine technology
- Rail vehicle technology
- Municipal services
- Iron and steel industry

Application tips

Apply OKS 2800 to the point to be tested by using the Airspray System OKS 5000, hand-sprayer or brush. Spray OKS 2801 on. A leak is indicated by the formation of foam bubbles. Caution: When using on polyamide lines, wash off with water after the test. Protect packaging against frost.



OKS 2801
Leak Detector, Spray

Packaging

- 400 ml Spray

Technical Data

	Standard	Conditions	Unit	Value
Main components				
basis				water
additives				corrosion protection
additives				active ingredients
Application related technical data				
lower operating temperature	DIN 51 805		°C	0
upper operating temperature	DIN 51 821-2		°C	50
colour				transparent
density (at 20°C)	DIN EN ISO 3838		g/cm ³	1
Properties and approvals				
DVGW approval	DIN EN 14 292			Reg.-Nr. NG-5170AO0659

OKS Spezialschmierstoffe GmbH

Ganghoferstraße 47
 82216 Maisach
 Phone: +49 (0) 8142 3051 - 500
 info@oks-germany.com
 www.oks-germany.com



The information in this publication reflects state-of-the-art technology, as well as extensive testing and experience. Due to the diversity of possible applications and technical realities, they can only serve as recommendations and are not arbitrarily transferable. Therefore, no obligations, liability or warranty claims can be derived from them. We only accept liability for the suitability of our products for particular purposes, and for certain properties of our products, in the event that we have accepted such liability in writing in the individual case. Any case of justified warranty claims shall be limited to the delivery of replacement goods free of defects, in the event that this subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular the liability for consequential injuries or damage, shall always be excluded. Prior to use, the customer must conduct its own testing to prove suitability. The data are subject to change for the sake of progress. ® = Registered trademark
Safety data sheet for industrial and commercial users is available for downloading under www.oks-germany.com. Our Customer and Technical service will be pleased to help should you have any further questions.