



Previous Name: Shell Spirax ASX 75W-140

Shell Spirax S6 AXME 75W-140

Superior performance, extended drain synthetic axle oil for Meritor, Scania and others

Shell Spirax S6 AXME 75W-140 is a unique fuel-efficient, long life transmission and axle oil, designed to provide ultimate protection to the latest heavy duty manual transmissions and axles. Specially formulated with synthetic base oils and additive technology unique for Shell, gives improved lubrication of the drive train, lowers the operating temperature and helps promote longer life for the equipment. Spirax S6 AXME 75W-140 is also extended oil drain capable and is approved by several OEMs for their extended drain specifications.

Performance, Features & Benefits

- Greater efficiency and therefore higher fuel economy
Tailored frictional properties give lower power loss and hence lower operating temperatures resulting in increased mechanical efficiency.
- Longer oil drain capability
Super high performance additives with exceptional oxidation resistance plus lower operating temperatures ensures long term gear and seal protection and longer oil life.
- Longer equipment life
Excellent protection against gear wear and pitting, helps prevent premature failures. Outstanding oxidation resistance also helps prevent damage to seals due to deposit formation.
- Less lubricant usage
Excellent static and dynamic seal compatibility exceeding OEM requirements, which helps minimize seal leaks. The extended drain capabilities help maximize oil drain intervals resulting in less overall lubricant usage during life of the equipment.
- Recognised by leading equipment manufacturers

Main Applications



- **Transmissions and axles**
Heavily loaded axles and non-synchronised transmissions where mineral and synthetic gear oils are recommended.

Specifications, Approvals & Recommendations

- Scania STO 2:0A
- SAE J2360
- API GL-5, MT-1
- MIL-PRF-2105E

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Helpdesk, or the OEM Approvals website.

Typical Physical Characteristics

Properties			Method	Shell Spirax S6 AXME 75W-140
SAE Viscosity Grade			SAE J 306	75W-140
Kinematic Viscosity	@40°C	mm ² /s	ISO 3104	172.4
Kinematic Viscosity	@100°C	mm ² /s	ISO 3104	24.5
Dynamic Viscosity	@-40°C	mPa s	ISO 9262	135000
Shear Stability (Viscosity after shearing)	@100°C	mm ² /s	CEC L-45_A-99 ISO 3104	24.3
Viscosity Index			ISO 2909	174
Density	@15°C	kg/m ³	ISO 12185	869
Flash Point (COC)			ISO 2592	210
Pour Point			ISO 3016	-45

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

■ Health and Safety

Shell Spirax S6 AXME 75W-140 is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from <http://www.epc.shell.com/>

■ Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Additional Information

■ Advice

Advice on applications not covered here may be obtained from your Shell representative.