



TRACTAGRI HDZ 15W-40



“Low-SAPS” lubricant especially developed for engines used in **tractors** and **agricultural equipments**, with or without **Diesel particulate filters**.

SPECIFICATIONS AND APPROVALS

International specifications	ACEA E9/E7	API CK-4/CJ-4/CI-4 plus/CI-4/SN
Manufacturers’ approvals ✓ Cummins CES 20086 ✓ MB-Approval 228.31 ✓ Deutz DQC III-10 LA ✓ Volvo VDS-4.5 approval Suitable for the engines of the following machines: ✓ CLAAS, FENDT, MASSEY-FERGUSON, SAME, McCORMICK, VALTRA...	Meets the requirements of ✓ CATERPILLAR ECF-3/ECF-2/ECF-1a ✓ CNH MAT 3521 Suitable when the following specifications are recommended ✓ JOHN DEERE JDQ 78X	

APPLICATIONS

TOTAL TRACTAGRI HDZ 15W-40 has been especially developed for **agricultural Diesel engines** that meet **European standard Stage IV** and **American standard EPA Tier 4 final** or previous emission standards. It is also suitable for the latest generation Diesel engines requesting an **API CK-4** level.

Thanks to its **“low-SAPS”** (low Sulphated Ash, Phosphorus and Sulphur) technology, TOTAL TRACTAGRI HDZ 15W-40 is designed for the latest Diesel engines equipped with **post-treatment systems**, such as Diesel particulate filters (DPF).

TOTAL TRACTAGRI HDZ 15W-40 is recommended, **throughout the year**, for engines of **tractors, harvesters** and **other agricultural equipments**. This lubricant is adapted to **all engines** of old or recent generation regardless to any **brands or types**.

PERFORMANCES AND CUSTOMER BENEFITS

TOTAL TRACTAGRI HDZ 15W-40 exhibits **excellent thermal stability** ensuring efficient lubrication of hot engine parts during severe and long working periods, even in summer.

Its **high viscosity** resists to high pressure between engine pieces and supports an eventual fuel dilution.

The advanced **“low-SAPS”** formulation of TOTAL TRACTAGRI HDZ 15W-40 helps prevent the clogging of the Diesel particulate filter (DPF) and extends the post-treatment system durability.

PHYSICAL AND CHEMICAL CHARACTERISTICS*

TOTAL TRACTAGRI HDZ 15W-40		Method	Value
Density at 15 °C	kg/m ³	ASTM D1298	877
Kinematic Viscosity at 40 °C	mm ² /s	ASTM D445	118
Kinematic Viscosity at 100 °C	mm ² /s	ASTM D445	15.5
Viscosity Index	-	ASTM D2270	138
Pour Point	°C	ASTM D97	-30
T.B.N	mgKOH/g	ASTM D2896	10
Sulphated Ash	% m/m	ASTM D874	0.99

* The features mentioned above are average values obtained with some variability in production and do not constitute a specification.

TOTAL LUBRIFIANTS
562, avenue du Parc de l’Ile
92029 Nanterre cedex
FRANCE

TOTAL TRACTAGRI HDZ 15W-40
Update 03/2020
www.lubricants.total.com



This lubricant does not cause adverse health effects when used in the intended application.
A safety datasheet is accessible on request from your local dealer or on the website www.quickfds.com